# 40 PLATINUM COURT THRUGOONA NSW 2640

H000
H001
H002
H100
H101
H102
H200

## PIPEWORK

	SANITARY DRAINAGE
	STORMWATER
SRM	SEWER RISING MAIN
<b>— —</b> cv <b>— — —</b> cv <b>— — —</b> cv	CHAMBER VENT
	VENT
CIS	PIPEWORK CAST IN SLAB
·	COLD WATER
	HOT WATER
· · ·	HOT WATER RETURN
	GAS
	GAS FLUE
FH	FIRE HYDRANT
———— FS ————	FIRE SERVICE
	PUMP OUT
— — RW — — — RW — — —	RAINWATER

EXISTING	PIPEWORK	

——————————————————————————————————————	EXISTING AUTHORITIES WATER MAIN
ES	EXISTING AUTHORITIES SEWER MAIN
——————————————————————————————————————	EXISTING AUTHORITIES GAS MAIN
— EASWM — — — EASWM — — —	EXISTING AUTHORITIES STORMWATER MAIN

## ABBREVIATIONS

AAV	AIR ADMITTANCE VALVE	Lt	LITR
AFFL	ABOVE FINISHED FLOOR LEVEL	NTS	NOT
AD	AERIAL DRAINAGE	NPCW	NON
В	BASIN	OFG	OVE
BTH	BATH	OSD	ONS
BT	BOUNDARY TRAP	PD	PLA
CICL	CAST IRON CEMENT LINED	PG	PLA
CO	CLEAROUT	RPZD	RED
CVP	CHAMBER VENT PIPE	RV	REL
CW	COLD WATER	RWT	RAIN
DB	DISABLED BASIN	RWO	RAIN
DWC	DISABLED WATER CLOSET	S	STA
DDCV	DOUBLE DETECTOR CHECK VALVE	SK	KITC
DP	DOWNPIPE	SHR	SHO
FE	FIRE EXTINGUISHER	SRM	SEW
FH	FIRE HYDRANT	SST	SOIL
FHR	FIRE HOSE REEL	STW	STO
FW	FLOOR WASTE	TMV	THE
GAVP	GREASE ARRESTOR VENT PIPE	TV	TEM
H/L	HIGH LEVEL	TD	TUN
HT	HOSE TAP	TTD	TRA
HR	HYDRAULIC RISER	TW	TRA
HWF	HOT WATER FLOW	TWV	TRA
HWR	HOT WATER RETURN	UR	URIN
HW	HOT WATER	VP	VEN
HWU	HOT WATER UNIT	WC	WAT
IPMF	IN-PIPE MICAFLAP	WM	WAS
LT	LAUNDRY TUB	W/M	WAT

WP

OT TO SCALE ON POTABLE COLD WATER VERFLOW GULLY **NSITE DETENTION** ANTER DRAIN ANTER GRATE EDUCED PRESSURE ZONE DEVICE ELIEF VENT AINWATER TANK **AINWATER OUTLET** ACK SYSTEM TCHEN SINK IOWER WER RISING MAIN DIL STACK ORMWATER IERMOSTATIC MIXING VALVE **EMPERING VALVE** JNDISH RAP TUNDISH RADE WASTE RADEWASTE VENT RINAL INT PIPE ATER CLOSET ASHING MACHINE ATER METER WATER POINTS

DRA	INA	GE

BTFW 🖾

SMH

H001

XXX XX

XXX XX

XXX XX

XXX

 $/A \setminus$ 

то D	TUNDISH
RV 🖸	REFLUX VALVE IN PIT
RV N	REFLUX VALVE
AAV 🛇	AIR ADMITTANCE VALVE
BT 🅱	BOUNDARY TRAP
CO 🏈	CLEAR OUT
CPC 🔘	CHROME PLATED CLEAROUT COVER
FW Ø	FLOOR WASTE
BTFW 🖪	BASKET TRAP FLOOR WASTE
SMH ()	SEWER MANHOLE
ORG	OVERFLOW RELIEF GULLY
IPMF	INDUCT PIPE MICA FLAP
SIP	SEWER INSPECTION PIT (SEALED)
CP	CONTROL PANEL
DTU 🕥	DRAINAGE TURN UP
0/F	OVERFLOW

### MISCELLANEOUS

DRAWING CONTINUATION
SERVICES IDENTIFIER - NON-DIRECTIONAL
SERVICES IDENTIFIER - DOWNWARD FLOW
SERVICES IDENTIFIER - UPWARD FLOW
 -SERVICE TYPE
 -SERVICE SIZE
DETAIL TAG
REVISION TAG

# NEW WAREHOUSE

# HYDRAULIC SERVICES

## DRAWING SCHEDULE:

NUMBER	TITLE
H000	COVERSHEET, LEGENDS, NOTES AND DRAWING LIST
H001	HYDRAULIC SPECIFICATIONS
H002	SITE SERVICES
H100	GROUND FLOOR PLAN SANITARY DRAINAGE LAYOUT
H101	MEZZANINE FLOOR PLAN SANITARY DRAINAGE LAYOUT
H102	ROOF PLAN SANITARY DRAINAGE LAYOUT
H200	GROUND FLOOR PLAN WATER AND GAS LAYOUT
H300	DETAILS

#### **COLD & HOT WATER SERVICE**

PUMP

 $\geq$ 

 $\rangle\rangle$ 

М

TMV

KKK

BUTTERFLY VALVE

PRESSURE LIMITING VALVE

BACKFLOW PREVENTION

BALANCING VALVE

HOSE TAP

WATER METER

COLD WATER POINT

PRESSURE REDUCTION VALVE

THERMOSTATIC MIXING VALVE

HOT AND COLD WATER POINTS

REDUCED PRESSURE ZONE DEVICE

FLOAT VALVE

#### **GAS SERVICE**

$\bowtie$	STOP VALVE	®	GAS REGULATOR
	PATH VALVE	GG OO	GAS GUARD
$X_{co}$	SOLENOID VALVE	×	GAS STOP VALVE
Ν	CHECK VALVE		GAS BALL VALVE
	REFLUX VALVE IN PATH BOX		
$\boxtimes$	FILTER		GAS BAYONET
PS I	PRESSURE SWITCH		GAS METER
Þ	STRAINER	$\boxtimes$	FILTER
0			

#### ABBREVIATIONS, SYMBOLS AND LINETYPES IN THE LEGEND MAY NOT APPEAR ELSEWHERE ON THE DRAWINGS. THIS LEGEND SHOULD BE USED AS A GUIDE ONLY

#### **DBYD CLAUSE**

CONTRACTOR IS RESPONSIBLE TO DETERMINE EXACT LOCATION OF THE SERVICE MAINS & TAKE EXTRA CARE DURING EXCAVATION TO ENSURE THE PREVENTION OF DAMAGE TO ANY UNDERGROUND ELECTRICAL, COMMUNICATION, WATER, GAS MAIN & DRAINAGE MAINS. REVIEW AND FOLLOW ALL DBYD PLANS.

#### **GENERAL REQUIREMENTS**

- 1. THE HYDRAULIC CONTRACTOR SHALL ALLOW FOR ALL SITE INVESTIGATIONS AND INSTALLATION OF COMPLETE AND COMPLIANT HYDRAULIC SERVICES SYSTEMS
- THE WORKS SHALL COMPRISE THE SITE INVESTIGATIONS, DESIGN, INSTALLATION CONSTRUCTION, DETAILING AND DOCUMENTATION, CO-ORDINATION, SUPPLY DELIVERY, PUTTING INTO SERVICES, PREPARATION OF SHOP DRAWINGS, SITE PAINTING, IDENTIFICATION, LABELLING, TESTING, COMMISSIONING, CERTIFICATIONS DEFECTS LIABILITY, WARRANTIES, MAINTENANCE AND AS BUILT DRAWINGS FOR THE HYDRAULIC SERVICES.
- 3. THE WORKS UNDER THE CONTRACT SHALL INCLUDE ALL THOSE MINOR WORKS NOT EXPLICITLY SPECIFIED AND WHICH ARE REASONABLY OBVIOUSLY NECESSARY AS PART OF THE WORKS.
- 4. PRIOR TO SUBMITTING TENDER THE CONTRACTOR SHALL INSPECT THE SITE TAKING INTO ACCOUNT ANY CONDITION LIKELY TO AFFECT THIS CONTRACT. CONTRACTOR SHALL INCLUDE PROVISIONS OF ANY ALTERATIONS / ADJUSTMENTS TO THE HYDRAULIC SERVICES AS REQUIRED TO SUIT THE BASE BUILDING SYSTEM INCLUSIVE OF EXISTING STRUCTURAL PENETRATIONS (IF ANY) AND OTHER TENANCY WORKS. FORMING PART OF THE TENDER SUBMISSION, CONTRACTOR SHALL ADVISE IN WRITING ANY ALTERATIONS / ADJUSTMENTS REQUIRED TO THE HYDRAULIC SERVICES INSTALLATIONS.
- INCORPORATE ALL COSTS AND ALLOWANCE FOR THE WORKS, ANY CUTTING IN. CONNECTIONS, ALTERATIONS TO THE EXISTING HYDRAULIC SERVICES SYSTEMS INCLUSIVE OF TESTING AND COMMISSIONING WHICH MAY BE REQUIRED TO BE UNDERTAKEN OUTSIDE NORMAL WORKING HOURS OR ON WEEKENDS.
- 6. UNDERTAKE ALL REQUIRED SITE INDUCTIONS AS PER BUILDING MANAGEMENT REQUIREMENTS. LIAISE WITH THE BUILDING MANAGEMENT PRIOR TO COMMENCEMENT OF WORK.
- PRIOR TO ISOLATING ANY SYSTEMS, NOTIFY THE BUILDING MANAGEMENT AND OBTAIN THE RELEVANT PERMIT TO COMPLETE THE ISOLATION. THE SYSTEM SHALL BE RETURNED TO NORMAL OPERATIONAL STATUS ON COMPLETION. BUILDING MANAGEMENT MUST BE INFORMED IN ADVANCE AND ANY CONDITIONS IMPOSED BY THE BUILDING MANAGEMENT SHALL BE MET BY THE CONTRACTOR AT THEIR EXPENSE.
- NO WORK THAT INVOLVES THE ISOLATION OR DISRUPTION OF THE HYDRAULIC 8 SERVICES MAY TAKE PLACE UNTIL THE BUILDING MANAGEMENT HAS GIVEN WRITTEN APPROVAL.
- ALL SYSTEMS AND EQUIPMENT SHALL BE FULLY TESTED IN ACCORDANCE WITH THE 9 RELEVANT STANDARDS, CODES AND THE REQUIREMENTS OF THE LOCAL SUPPLY AUTHORITY. ANY OTHER TESTS DEEMED NECESSARY SHALL BE CARRIED OUT.
- 10. AFTER COMPLETION OF ALL THE TESTS AND CHECKS, PROVIDE STANDARD CERTIFICATES OF COMPLIANCE FOR BUILDING SAFETY SERVICES AS REQUIRED BY THE PRINCIPAL CERTIFYING AUTHORITY FOR THE PROVISION OF CERTIFICATES OF OCCUPANCY.
- 11. TENDERER SHALL TAKE SPECIAL NOTICES OF THE LOCATION OF THE PROPOSED WORKS WITH THE DELIVERY AND ACCESS FOR DELIVERIES.
- 12. VARIATION SUBMISSIONS RESULTING FROM THE FAILURE TO ADEQUATELY ASSESS THE EXISTING INSTALLATION DURING THE TIME OF TENDER SHALL BE REJECTED.

## **MISCELLANEOUS**

- PIPE RISER 0 С PIPE DROPPER PIPE TEE PIPEWORK CONTINUATION FLOW DIRECTION NEW TEE IN EXISTING PIPEWORK Н NEW CONNECTION TO EXISTING PIPEWORK \_ FIRE HOSE REEL 囯
- FIRE HYDRANT Ø
- FIRE EXTINGUISHER
- 1 NODE POINT
- PENETRATION  $\succ$
- PIPE END SECTION



CENTRIC BUILDING SERVICES ENGINEERS PTY LTI his drawing is the property of Centric Building Services PTY must not be used, reproduced or copied wholly c part without the written permission of Centric Build rvices Pty Limited. The elements shown on this drawing ar otypical design only. The contractor shall produc orkshop drawings for construction purposes. The contracto hall not scale from this drawing and all measurements shall be

# HYDRAULIC SERVICES

**NS** 2 EW Ζ


# 0 RU 0

0

Project Number: 24071 Drawing Number: Hooo Revision:

P1

Sydney: (02) 9052 6460 Newcastle: (02) 9052 6461



 $\checkmark$ info@centricengineers.com.au www.centricengineers.com



GENERAL NOTES:

- 1. THESE DRAWINGS ARE A GUIDE ONLY FOR THE LOCATION AND LAYOUT OF THE SERVICE PIPES. CONTRACTOR TO EXAMINE SITE CONDITIONS AND ROUTE PIPEWORK TO MOST APPROPRIATE LOCATION ON SITE
- 2. THESE DRAWINGS ARE TO BE READ IN CONJUNCTION WITH ALL OTHER CONTRACT DOCUMENTS, SPECIFICATIONS AND DRAWINGS. FOR THE FINAL LOCATION OF FIXTURES AND FITTINGS REFER TO ARCHITECTURAL SCHEDULE AND DRAWING PACKAGE.
- 3. THE HYDRAULIC SERVICES WORK SHALL BE CARRIED OUT UNDER THE DIRECT SUPERVISION OF A LICENSED PLUMBER, DRAINER AND GAS FITTER IN STRICT ACCORDANCE WITH THE NSW CODES OF PRACTICE PLUMBING AND DRAINAGE, NATIONAL CONSTRUCTION CODE, RELEVANT AUSTRALIAN STANDARDS, COUNCIL REGULATIONS, FIRE ENGINEERING REPORT WHERE APPLICABLE AND TO THE SATISFACTION OF THE CONTROLLING AUTHORITIES.
- 4. THIS SET OF DRAWINGS IS DIAGRAMMATIC ONLY. THE CONTRACTOR SHALL CO-ORDINATE WITH OTHER TRADES AND SET OUT ALL WORKS TO SUIT ACTUAL ON-SITE CONDITIONS.
- 5. THIS SET OF DRAWINGS IS ISSUED FOR TENDER STATUS FOR THE WORKS WHICH DOES NOT CONSTITUTE AS THE INSTALLATION DRAWINGS. THE CONTRACTOR SHALL DEVELOP THE INFORMATION CONTAINED ON THIS SET OF DRAWINGS INTO A COMPLETE SET OF FULLY DETAILED INSTALLATION DRAWINGS FOR CONSTRUCTION.
- 6. CONFIRM LOCATION, SIZES AND DEPTHS OF STRUCTURAL BEAMS, ALL OTHER SERVICES, CEILING VOID AND CEILING HEIGHT PRIOR TO INSTALLATION. DETERMINE EXACT SIZES AND LOCATIONS OF STRUCTURAL PENETRATIONS ON SITE IN ACCORDANCE WITH THE STRUCTURAL REQUIREMENTS. OBTAIN APPROVAL FROM STRUCTURAL ENGINEER PRIOR TO DRILLING ANY CORE HOLES AND PENETRATING STRUCTURE.
- 7. DISTURBED AREAS ARE TO BE REINSTATED TO THE ORIGINAL CONDITION. TRENCHES THROUGH EXISTING ROAD AND CONCRETE SHALL BE FILLED AND COMPACTED AS PER STRUCTURAL ENGINEER'S REQUIREMENTS.
- 8. OBTAIN APPROVALS, PERMITS AND FINAL CERTIFICATES FROM CONTROLLING AUTHORITIES PRIOR TO THE COMPLETION OF WORKS.
- 9. PAY ALL APPLICABLE FEES AND CHARGES INCLUDING AREA CONTRIBUTION IN ACCORDANCE WITH CONTROLLING AUTHORITIES CURRENT FEE SCALES. SUBMIT DETAILED HYDRAULIC CALCULATIONS WITH ISOMETRIC DIAGRAMS FOR THE HYDRAULIC SERVICES SYSTEMS FOR REVIEW PRIOR TO INSTALLATION.
- 10. TECHNICAL SUBMISSION INCLUDING SHOP DRAWINGS, MATERIAL / EQUIPMENT SCHEDULES WITH TECHNICAL INFORMATION, HYDRAULIC CALCULATIONS, BMS SCHEDULES AND SAMPLES SHALL BE SUBMITTED TO CENTRIC FOR REVIEW PRIOR TO INSTALLATION.
- 11. ALL HYDRAULIC SERVICES PIPEWORK SHALL BE LOCATED IN CEILINGS, WALLS, DUCTS OR UNDER BENCHES. PIPEWORK INSTALLED OTHER THAN NOTED SHALL BE APPROVED BY THE SUPERINTENDENT BEFORE WORK IS INSTALLED.

- 1. VERIFY THAT ALL INVERT LEVELS, SURFACE LEVELS AND CLEARANCES ARE CORRECT AND OBTAINABLE PRIOR TO COMMENCING WORKS.
- 2. ALL LEVELS ARE SHOWN IN METRES AHD. UNLESS NOTED OTHERWISE.

#### **REGULATIONS:**

- 1. ALL WORKS TO BE CONSTRUCTED IN ACCORDANCE WITH NSW CODES OF PRACTICE, NATIONAL CONSTRUCTION CODE, RELEVANT AUSTRALIAN STANDARDS, COUNCIL REGULATIONS, AND WHERE APPLICABLE AND TO THE SATISFACTION OF THE CONTROLLING AUTHORITIES.
- 2. WORKS SHALL BE CONSTRUCTED & INSTALLED BY SUITABLY QUALIFIED, LICENSED, AND COMPETENT TRADES PERSONNEL.
- 3. ALL WORKS RELATING TO NSW EDUCATION SHALL BE IN ACCORDANCE WITH THE EFSG GUIDELINES.

#### **TESTING AND INSPECTION**

- 1. THE CONTRACTOR SHALL PAY ALL COSTS FOR TESTING OF HYDRAULIC SERVICES. ALL TESTING PROCEDURES TO BE UNDERTAKEN AS PER THE RELEVANT AUSTRALIAN STANDARD AND OR AUTHORITY REQUIREMENTS.
- 2. THE CONTRACTOR SHALL ARRANGE INSPECTIONS WITH THE APPROPRIATE AUTHORITIES PRIOR TO SEALING OF SERVICES AT EACH STAGE WHERE REQUIRED.

#### EXISTING SERVICES

1. ALL EXISTING SERVICES MADE REDUNDANT FROM THESE WORKS AND EXISTING REDUNDANT SERVICES SHALL BE REMOVED OR SEALED OFF IN ACCORDANCE WITH THESE DRAWINGS, CONTRACT DOCUMENTS AND TO THE SATISFACTION OF THE LOCAL AUTHORITY.

#### PIPE DIAMETERS

- 1. ALL PIPE DIAMETERS DETAILED ON THESE DRAWINGS ARE SHOWN AS NOMINAL DIAMETERS(DN).
- 2. WHERE PE, PEX, PPR, PB AND COMPOSITE PLASTIC PIPEWORK MATERIALS ARE NOMINATED, THE NOMINAL DIAMETER SHALL BE TAKEN AS THE INTERNAL DIAMETER OF THE PIPEWORK AND NOT THE OUTSIDE DIAMETER. FOR NOMINAL DIAMETERS UP TO DN50, REFER TO AS/NZS3500.1.

FIRE RATED PENETRATIONS

- 1. PROVIDE FIRE RATED PENETRATIONS FOR SERVICES PASSING THROUGH EACH FIRE RATED ELEMENT. FIRE RATED PENETRATIONS SHALL ACHIEVE THE SAME RATING AS THE BUILDING ELEMENT PENETRATED. SEAL PENETRATIONS WITH A SYSTEM CONFORMING TO AS4072.1. PASSIVE FIRE ENGINEER AND NCC.
- 2. WHEREVER OR WHENEVER THE PROPOSED WORKS REQUIRE THE PENETRATION OF AN ELEMENT HAVING A FIRE RESISTANCE RATING, THE CONTRACTOR SHALL ENSURE THAT ANY PERSON RESPONSIBLE FOR THE INSTALLATION OF ANY SYSTEM USED TO PROTECT/REINSTATE THE FRL OF THE PENETRATION;
- HOLDS AN APPROPRIATE LICENSE PROVIDES AN INSTALLATION STATEMENT IN THE FORMAT PRESCRIBED BY AS4072.1 TO
- DESCRIBE THE PENETRATION, ITS LOCATION AND METHOD OF TREATMENT; THE CONTRACTOR SHALL FURNISH A COPY OF THE INSTALLATION STATEMENT AS PROVIDED IN ABOVE TO THE INSPECTING OFFICER PRIOR TO REQUESTING AN INSPECTION FOR 'SUBSTANTIAL COMPLETION'.
- 3. PROVIDE ACCESS TO PASSIVE FIRE PROTECTION DEVICES FOR INSPECTION IN ACCORDANCE WITH AS1851.
- 4. CONTRACTOR TO ENSURE THAT A QUALIFIED PASSIVE FIRE PROTECTION COMPANY IS ENGAGED TO CERTIFY THE FINAL INSTALLATION OF ANY INSTALLED PASSIVE FIRE PROTECTION MEASURES THAT ARE PART OF THIS SCOPE OF WORKS.

#### THERMAL INSULATION OF PIPEWORK

- 1. THERMAL INSULATION SHALL COMPLY IN ALL RESPECTS WITH AS/NZS3500.4.
- 2. FOR INSULATED PIPING, COMPLETELY COVER THE PIPE WITH INSULATION FITTED TIGHTLY TO THE PIPE SURFACE AND SECURED AS PER MANUFACTURES REQUIREMENTS. INSTALL INSULATION SO THAT IT IS READILY REMOVABLE AT UNIONS AND COUPLERS.
- 3. PROVIDE METAL SHEATHING TO INSULATION WHERE PIPEWORK IS IN PLANT ROOMS AND, EXTERNAL LOCATIONS. METAL SHEATHING INSTALLED TO MANUFACTURES REQUIREMENTS.
- 4. PROVIDE THERMAL INSULATION TO ALL DOMESTIC WATER PIPEWORK, INCLUDING COLD WATER. ENSURE COLD WATER PIPEWORK IS CONTINUOUSLY VAPOUR PROOFED INSULATED.

#### ACOUSTIC TREATMENT OF PIPEWORK

1. ACOUSTIC REDUCTION TREATMENT SHALL BE PROVIDED IN AREAS REQUIRED BY THE NCC. ALL HYDRAULIC PIPES SHALL BE ACOUSTICALLY TREATED WHERE REQUIRED.

#### O AND M MANUALS/COMMISSIONING:

- 1. PRIOR TO PRACTICAL COMPLETION PROVIDE FULLY COMPREHENSIVE SET OF OPERATING AND MAINTENANCE MANUALS. THE CONTENT OF THE MANUALS SHALL MINIMALLY COMPRISE THE FOLLOWING:
- LOCAL AUTHORITIES CERTIFICATE OF FINAL INSPECTION & APPROVAL. OPERATING INSTRUCTIONS FOR SPECIFIC PLANT THAT REQUIRES DAY TO DAY OPERATIONS BY PERSONNEL
- MAINTENANCE INSTRUCTION AS RECOMMENDED BY THE EQUIPMENT SUPPLIER FOR EQUIPMENT AND PLANT THAT IS LIABLE TO FAILURE WITHOUT SUCH MAINTENANCE MANUFACTURES BROCHURES, PROVIDING VISUAL RECOGNITION OF EACH COMPONENT OF
- ASSEMBLY AS WELL AS NAME OF MANUFACTURER AND ADDRESS FOR PROCUREMENT. MANUALS ARE TO BE FULLY BOUND IN BOOK FORM COMPRISING OF A4 SHEETS OR A3 SHEETS SUITABLY FOLDED. LARGER SHEETS OR DRAWINGS ARE TO BE ENCLOSED IN CLEAR
- VINYL SLEEVES. SHEETS AND SLEEVES ARE TO BE PUNCHED AND CONTAINED IN QUALITY VINYL FOLDERS LABELLED ON THE OUTSIDE FRONT COVER AND ON THE SPINE TO INDICATE THE NAME OF THE PROJECT, CLIENT AND THE SERVICES DESCRIBED THEREIN. COPIES OF WARRANTY REGISTRATION CERTIFICATES FOR EACH ITEM OF EQUIPMENT.
- LOG SHEET FOR RECORDING; THE TESTING OF BACK FLOW PREVENTION DEVICES, TEMPERING VALVES AND THERMOSTATIC MIXING VALVES, THE LOG SHEET DETAIL AND THE TEST PROCEDURES AND MAINTENANCE OF ALL VALES. THE LOG SHEET DETAIL. AND THE
- TEST PROCEDURES AND MAINTENANCE OF ALL VALVES, ALONG WITH LIST OF FUTURE TEST DATES. ORIENTATE AND ADJUST HYDRAULIC SERVICES TO SUIT FINAL LAYOUTS OF THE AMENITIES, TENANCY PLANS AND PLANTS.
- 2. ALL EQUIPMENT AND APPLIANCES SHALL BE INSTALLED TO THE MANUFACTURERS REQUIREMENTS.

### OCCUPATIONAL HEALTH AND SAFETY:

- 1. FOR RESIDUAL RISKS IDENTIFIED FROM THE DESIGN PROCESS, REFER TO THE PROJECT RISK REGISTER.
- 2. CHANGES TO HYDRAULIC SERVICES DESIGN SHALL BE REVIEWED AGAINST THE PROJECT RISK REGISTER AND MAY REQUIRE FURTHER RISK ASSESSMENT.

#### PLUMBING AND DRAINAGE:

1. SUPPLY, INSTALL, TEST AND COMMISSION ALL SEWER DRAINAGE FROM SOIL AND WASTES AND FIXTURES TO THE SEWER CONNECTION. PROVIDE ALL NECESSARY PIPES, JUNCTIONS, BENDS. PITS, FLOOR WASTES, EXCAVATION, SUPPORTS, BACKFILLING, TESTING, AND SUNDRY EQUIPMENT REQUIRED FOR THE INSTALLATION. PIPELINE POSITIONS SHALL BE DETERMINED ON SITE IN CONJUNCTION WITH ALL OTHER DISCIPLINES TO ENSURE ADEQUATE COORDINATION OF ALL SERVICES AND ELEMENTS. COORDINATION SHALL BE CARRIED OUT PRIOR TO ANY SETTING OUT, EXCAVATION AND PIPE INSTALLATION TAKING PLACE.

- 2. PROVIDE IDENTIFICATION TO ALL SERVICE PIPES AND CONDUITS EXPOSED TO VIEW OR IN ACCESSIBLE LOCATIONS SUCH AS DUCTS AND CEILING SPACES AND ALL EQUIPMENT.
- 3. ALL PIPES SHALL BE ADEQUATELY SUPPORTED AND SECURELY FIXED IN ACCORDANCE WITH THE DRAWINGS AND TO THE SATISFACTION OF THE SI. SUCH SUPPORTING AND FIXING TO BE CARRIED OUT WITHOUT CAUSING ANY DISTORTION, DAMAGE OR STRESS ON THE PIPES OR PIPE JOINTS. PIPES SHALL BE SUPPORTED SPECIFIED IN "PRELIMINARIES" SECTION.
- 4. FIXTURE TRAPS: - SINKS - 50mm TWO-PART UNIVERSAL PATTERN.
- BASIN 40mm CP COPPER TWO-PART S OR P TRAP WITH 40mmCP EXTENSION RISER.
- 5. TERMINATE ALL VENTS THROUGH ROOF WITH A VENT COWL. FINISH VENTS 300mm ABOVE NON-TRAFFICABLE ROOFS AND 3m ABOVE TRAFFICABLE ROOFS, 6 METRES CLEAR OF OPENINGS AND FRESH AIR INTAKES AS REQUIRED BY THE LOCAL AUTHORITY AND AS INDICATED ON THE DRAWINGS
- 6. INSTALL INSPECTION OPENINGS IN ACCESSIBLE LOCATIONS SO THAT EACH SECTION OF PIPEWORK CAN BE CLEANED. INSPECTION OPENING SIZES SHALL BE IN ACCORDANCE WITH AUTHORITIES' REQUIREMENTS. INSTALL INSPECTION OPENINGS AS PER AS3500.2.
- 7. SUPPLY AND INSTALL UPVC TUNDISHES IN AREAS REQUIRED FOR MECHANICAL DRAINAGE TUNDISHES TO BE CHROME PLATED WHERE EXPOSED AND TO COMPLY TO "MATERIALS" SECTION.
- 8. SUPPORTING AND FIXING TO BE CARRIED OUT WITHOUT CAUSING ANY DISTORTION, DAMAGE OR STRESS ON THE PIPES OR PIPE JOINTS.

COLD WATER SERVICE:

- 1. SUPPLY, INSTALL, TEST AND COMMISSION ALL DOMESTIC COLD WATER PIPES FROM THE AUTHORITY'S MAIN TO ALL FIXTURES, FITTINGS AND FAUCETS REQUIRING DOMESTIC COLD WATER. INCLUDE FOR ALL PIPEWORK, BENDS, OFFSETS, BRACKETS, PUMPS, TAPS AND FAUCETS AND SUNDRY EQUIPMENT REQUIRED FOR THE INSTALLATION. REFER TO 'MATERIALS' SECTION FOR PIPING SCHEDULE.
- 2. APPLY TO WATER AUTHORITY FOR THE SUPPLY OF ALL METERS, TAKE DELIVERY FROM AUTHORITY'S STORE AND INSTALL ON SITE, COMPLETE WITH ALL VALVES AND FITTINGS REQUIRED
- 3. EXCAVATE, LOCATE, AND CONNECT TO THE EXISTING AUTHORITIES WATER MAINS FOR THE SERVICES AS REQUIRED AND EXTEND TO THE RETICULATION. CONTRACTOR TO APPLY, MAKE ALL RELEVANT APPLICATIONS AND PAY ALL ASSOCIATED FEES.
- 4. PROVIDE A WATER PRESSURE TEST OF 1500 KPA FOR A PERIOD OF TWO HOURS. DISCONNECT ANY EQUIPMENT CONNECT TO THE SERVICE NOT RATED TO THE TEST PRESSURE BEFORE TESTING COMMENCES.
- 5. HYDRAULICS SHALL FLUSH OUT, REMOVE ALL FOREIGN MATTER, AND CLEAN ALL THE SYSTEMS. WATER SYSTEMS SHALL BE FLUSHED OUT WITH CLEAN WATER.
- 6. PROVIDE AND INSTALL HOSE TAPS WITH ANTI-VANDAL HEADS. (WHERE REQUIRED)
- 7. ALL PIPES SHALL BE ADEQUATELY SUPPORTED AND SECURELY FIXED IN ACCORDANCE WITH AS3500.1

#### HEATED WATER SERVICE:

- 1. SUPPLY, INSTALL, TEST AND COMMISSION THE DOMESTIC HOT WATER SERVICE AND WARM WATER SERVICE FROM THE HOT WATER HEATERS TO THE FIXTURES AND APPLIANCES. INCLUDE FOR ALL PIPING, FITTINGS, SUPPORTS, INSULATION, HOT WATER HEATERS, VALVES, CIRCULATING PUMPS AND OTHER SUNDRY ITEMS OF EQUIPMENT REQUIRED FOR THE INSTALLATION.
- PROVIDE A WATER PRESSURE TEST OF 1500 KPA FOR A PERIOD OF TWO HOURS. DISCONNECT ANY EQUIPMENT CONNECTED TO THE SERVICE NOT RATED TO THE TEST PRESSURE BEFORE TESTING COMMENCES.
- 3. MAKE ADEQUATE PROVISION FOR EXPANSION AND CONTRACTION BY THE PROVISION OF CLIPS/BRACKETS WITH WOODEN EXPANSION BLOCKS SO THAT UNDER ALL WORKING CONDITIONS NO STRAIN IS IMPOSED ON PIPEWORK OR FITTINGS,
- 4. PROVIDE AIR RELIEF VALVES WITH TO PIPELINES AT THE TOP OF CIRCULATION LOOPS (FLOW AND RETURN) THAT DO NOT HAVE AN OUTLET AT THE HIGHEST POINT IN THE LOOP. EXTEND A 15MM DRAIN PIPELINE FROM THE VALVE TO A DRAINAGE POINT OR TUNDISH.
- 5. SUPPLY AND INSTALL AN ADJUSTABLE TEMPERING VALVE SET AT 50\*C TO ALL BASINS AND
- SHOWERS OR AREAS OF ABOLITION. 6. SUPPLY AND INSTALL THERMOSTATIC MIXING VALVES TO ALL ACCESSIBLE TOILETS AND ALL
- SANITARY FIXTURES, AS INDICATED ON THE DRAWINGS SET AT 450C. SUPPLY, INSTALL AND FIX HOT WATER HEATERS IN THE LOCATIONS INDICATED ON THE DRAWINGS. INSTALLATION OF HOT WATER HEATERS AS PER AS3500.4. TEMPERATURE PRESSURE RELIEF VALVE TO BE DIRECTED TO TUNDISH.
- 8. SUPPLY AND INSTALL BOILING WATER UNITS AS PER ARCHITECTURAL DOCUMENTATION.

#### FIRE HOSE REEL SERVICE:

- 1. SUPPLY, INSTALL, TEST AND COMMISSION THE HOSE REEL SERVICE FROM THE POINT OF CONNECTION TO ALL FIRE HOSE REELS ALL IN ACCORDANCE WITH THE NCC AND AS 2441. 2. SUPPLYING ALL FITTINGS, VALVES, BRACKETS, PUMPS AND SUNDRY ITEMS TO COMPLETE THE
- INSTALLATION INCLUDING THE HOSE REELS TO THE APPROVAL OF THE NSW FIRE BRIGADE, THE LOCAL COUNCIL AND THE SI. FIRE HOSE REELS TO BE INSTALLED WITHIN 4M OF EGRESS. 3. ON COMPLETION OF THE FIRE HOSE REEL INSTALLATION, PROVIDE 'TAGS' FOR ALL FIRE HOSE
- REELS AND ENGAGE A FIRE PROTECTION CONTRACTOR TO INSPECT THE HOSE REELS FOR COMPLIANCE. FLUSH SYSTEM TO REMOVE DEBRIS.

FIRE HYDRANT SERVICE:

- 1. SUPPLY, INSTALL, TEST AND COMMISSION THE FIRE HYDRANT SERVICE FROM THE INCOMING WATER MAIN TO ALL FIRE HYDRANTS REQUIRED. INCLUDE FOR ALL PIPING, FITTINGS, VALVES, HYDRANT VALVES, PUMPS, CONTROL EQUIPMENT ELECTRICAL WIRING AND OTHER SUNDRY ITEMS OF EQUIPMENT AS REQUIRED FOR THE INSTALLATION IN ACCORDANCE WITH THE NCC AND AS 2419. PROVIDE A FLOW TEST TO COMPLY TO AS2419.1.
- 2. PROVIDE DOUBLE CHECK DETECTOR VALVE ASSEMBLIES WITH DOUBLE CHECK DETECTOR VALVES AND BY-PASS METERS. DOUBLE CHECK DETECTOR ASSEMBLIES TO BE ZURN - 350DA OR APPROVED EQUAL AND INSTALLED UPSTREAM OF FIRE HYDRANT VALVE ASSEMBLIES.
- 3. SUPPLY AND INSTALL AN APPROVED FIRE HYDRANT BOOSTER VALVE IN ACCORDANCE WITH AS2419.1 & FPAA101H SPRINKLER SYSTEM.
- 4. SUPPLY AND INSTALL INTERNAL LANDING VALVE HYDRANTS IN APPROVED LOCATIONS WITH THE CENTRE OF THE VALVE 750MM ABOVE FLOOR AND HAVING AT LEAST 300MM CLEARANCE AND ANGLED 350 DOWN FROM THE HORIZONTAL PLANE. INSTALL HYDRANTS CLEAR OF FIRE EGRESS PATH
- 5. INSTALL FIRE HYDRANTS WHERE NOMINATED ON DRAWINGS.
- 6. TEST ALL PIPEWORK 1700 KPA FOR A PERIOD OF TWO HOURS. 7. ALL PIPES SHALL BE ADEQUATELY SUPPORTED AND SECURELY FIXED IN ACCORDANCE WITH THE DRAWINGS AND TO THE SATISFACTION OF THE SI. SUCH SUPPORTING AND FIXING TO BE CARRIED OUT WITHOUT CAUSING ANY DISTORTION, DAMAGE OR STRESS ON THE PIPES OR PIPE JOINTS. THE SUBCONTRACTOR SHALL PAY PARTICULAR ATTENTION TO ANY INTERNAL FIRE HYDRANT SUPPLY PIPING THAT IS TO BE INSTALLED WITHIN A NON-FIRE SPRINKLER PROTECTED SPACE / BUILDING. FIXINGS AND SUPPORTS ARE REQUIRED TO BE 60/-/- RATED IN ACCORDANCE WITH AS2419. EVIDENCE THAT THIS FIXING AND SUPPORT COMPLIANCE IS REQUIRED TO BE PROVIDED PRIOR TO INSTALLATION.
- 8. PROVIDE A BLOCK PLAN IN ACCORDANCE WITH AS 2419.1. IT SHALL BE FIXED WITHIN OR ADJACENT TO THE BOOSTER CABINET, ENCLOSURE, OR RECESS WHERE IT CAN BE READILY SEEN BY FIRE FIGHTERS AND OTHERS RESPONDING TO AN ALARM OR AT OTHER POSITIONS AS REQUIRED BY THE REGULATORY AUTHORITY.



© CENTRIC BUILDING SERVICES ENGINEERS PTY LTD This drawing is the property of Centric Building Services PT Limited and must not be used, reproduced or copied wholly or in part without the written permission of Centric Building Services Pty Limited. The elements shown on this drawing are prototypica design only. The contractor shall produce workshop drawings for construction purposes. The contractor shall not scale from this drawing and all measurements shall be carried out on site.

#### P1 30.05.2025 100% FINAL COORDINATION





Project North



Client: Architect:	VINCENT JARVIS
Project Number: Drawing Number: Revision:	
Drawn by: Designed by: Approved by: Scale:	IB IB JA NTS

NEW WAREHOUSE, 40 PLATINUM COURT, THRUGOONA, NSW, 2640


HYDRAULIC SPECIFICATIONS



Sydney: Suite 1, 401 Pacific Hwy Artarmon, NSW 2064 **Newcastle**: Suite 4, 102 Glebe Road The Junction, NSW 2291

info@centricengineers.com.au www.centricengineers.com







P1 30.05.2025 100% FINAL COORDINATION





Project North



Client: Architect:	VINCENT JARVIS
Project Number: Drawing Number: Revision:	
Drawn by: Designed by: Approved by: Scale:	IB IB JA 1:300 @ A1

NEW WAREHOUSE, 40 PLATINUM COURT, THRUGOONA, NSW,2640

SITE SERVICES


Sydney: (02) 9052 6460 Newcastle: (02) 9052 6461

**Sydney**: Suite 1, 401 Pacific Hwy Artarmon, NSW 2064 **Newcastle**: Suite 4, 102 Glebe Road The Junction, NSW 2291

0

 $\checkmark$ info@centricengineers.com.au www.centricengineers.com





HYDRAULIC CONTRACTOR TO TIE IN SEWER DRAINAGE WITH GROUND FLOOR SLAB AS PER APPROVED DESIGN AND RELEVANT STANDARDS. CONTRACTOR TO INSTALL PIPE FASTENERS AT MAXIMUM INTERVALS OF 1.5 METERS. THREADED RODS SHALL BE EXTENDED TO THE CENTER OF THE SLAB.

ALL SEWER DRAINAGE LINES SHALL BE SECURELY FASTENED TO THE SLAB TO PREVENT MOVEMENT AND ENSURE LONG-TERM STABILITY. ALL MATERIALS TO BE USED SHALL BE CORROSION-RESISTANT AND SUITABLE FOR THE INTENDED ENVIRONMENT.

-SIGHT SPLAY



© CENTRIC BUILDING SERVICES ENGINEERS PTY LTD This drawing is the property of Centric Building Services PTY Limited and must not be used, reproduced or copied wholly or in part without the written permission of Centric Building Services Pty Limited. The elements shown on this drawing are prototypical design only. The contractor shall produce workshop drawings for construction purposes. The contractor shall not scale from this drawing and all measurements shall be carried out on site.

#### P1 30.05.2025 100% FINAL COORDINATION

100% ISSUE



Project North



Client: Architect:	VINCENT JARVIS
Project Number: Drawing Number: Revision:	
Drawn by: Designed by: Approved by: Scale:	IB IB JA 1:100 @ A1

NEW WAREHOUSE, 40 PLATINUM COURT, THRUGOONA, NSW,2640

GROUND FLOOR PLAN SANITARY DRAINAGE LAYOUT

Sydney: (02) 9052 6460 Newcastle: (02) 9052 6461

0

**Sydney**: Suite 1, 401 Pacific Hwy Artarmon, NSW 2064 **Newcastle**: Suite 4, 102 Glebe Road The Junction, NSW 2291


 $\checkmark$ info@centricengineers.com.au www.centricengineers.com



Scale Bar

10 m







#### P1 30.05.2025 100% FINAL COORDINATION





Project North




Client: Architect:	VINCENT JARVIS
Project Number: Drawing Number: Revision:	
Drawn by: Designed by: Approved by: Scale:	IB IB JA 1:100 @ A1

NEW WAREHOUSE, 40 PLATINUM COURT, THRUGOONA, NSW,2640

LEVEL M FLOOR PLAN SANITARY DRAINAGE LAYOUT

Sydney: (02) 9052 6460 Newcastle: (02) 9052 6461



0


 $\checkmark$ info@centricengineers.com.au www.centricengineers.com





Scale Bar

10 m





P1 30.05.2025 100% FINAL COORDINATION






Project North



Client: Architect:	VINCENT JARVIS
Project Number: Drawing Number: Revision:	
Drawn by: Designed by: Approved by: Scale:	IB IB JA 1:100 @ A1

NEW WAREHOUSE, 40 PLATINUM COURT, THRUGOONA, NSW,2640

ROOF PLAN SANITARY DRAINAGE LAYOUT



0 **Sydney**: Suite 1, 401 Pacific Hwy Artarmon, NSW 2064 **Newcastle**: Suite 4, 102 Glebe Road The Junction, NSW 2291

 $\checkmark$ info@centricengineers.com.au www.centricengineers.com






Scale Bar

10 m

1:100 @ A1





#### P1 30.05.2025 100% FINAL COORDINATION





Project North



Client: Architect:	VINCENT JARVIS
Project Number: Drawing Number: Revision:	
Drawn by: Designed by: Approved by: Scale:	IB IB JA 1:100 @ A1

NEW WAREHOUSE, 40 PLATINUM COURT, THRUGOONA, NSW, 2640

GROUND FLOOR PLAN WATER AND GAS LAYOUT

> Sydney: (02) 9052 6460 Newcastle: (02) 9052 6461

> > $\square$



 $\sim$ info@centricengineers.com.au www.centricengineers.com





SUPPLY AND INSTALL NEW RHEEM ELECTRICAL 50L HOT WATER UNIT SET AT 60°C MODEL: 191 050 1  $\times$  1.8kW HOT WATER UNIT INSTALLED ON SAFE TRAY IN JOINERY, TPR TO DRAIN TO TUNDISH.

CONTRACTOR TO INSTALL HWC TUNDISH BY ALLPROOF INDUSTRIES IN A SAFE TRAY

25mm PIPE RISE FROM BELOW GROUND TO HIGH LEVEL. PIPE CLIPPED TO THE WALL.

FIRE HOSE REEL MOUNTED AT 1500mm AFFL WITHIN 4m OF EGRESS.

DUAL HEAD FIRE HYDRANT 750mm AFFL

PROVIDE STEEL CONCRETE FILLED BOLLARD PROTECTION AROUND FIRE HYDRANT

IN GROUND FIRE HYDRANT PIPEWORK TO BE PE100 RED STRIPE SDR11 PN16

> SUPPLY AND INSTALL 20mm HOSE TAP . MOUNT TO WEATHERPROOF POST.

SUPPLY AND INSTALL NEW 25mm WATER SERVICE WITH WATER METER BIFURCATED FROM 100mm SERVICE. SUPPLY NON TESTABLE DCV. CONTRACTOR TO APPLY, MAKE APPLICATION TO COUNCIL AND PAY ALL ASSOCIATED FEES.


- NEW 100mm WATER CONNECTION TO EXISTING WATER MAIN FOR FIRE AND POTABLE WATER SERVICES. CONTRACTOR TO APPLY TO COUNCIL AND PAY ALL ASSOCIATED FEES. ALLOW FOR ROAD CROSSING/UNDER-BORE.


SUPPLY AND INSTALL NEW 100mm DOUBLE CHECK VALVEDETECTOR ASSEMBLY EQUAL TO ZURN 350DA COMPLETE WITH 20mm BY-PASS.

— SIGHT SPLAY

Scale Bar

10 m







P1 30.05.2025 100% FINAL COORDINATION


100%

ISSUE

HYDRAULIC

SERVICES


Project North





NEW WAREHOUSE, 40 PLATINUM COURT, THRUGOONA, NSW,2640

DETAILS



0



info@centricengineers.com.au www.centricengineers.com



### **DOCUMENT REGISTER & TRANSMITTAL NOTICE**



Centric Building Services Engineers Pty Ltd

CENTRICENGINEERS<br/>Building ServicesSydney: Suite 1, 401 Pacific Hwy, Artarmon, NSW 2064<br/>Newcastle: Suite 4, 102 Glebe Road, The Junction, NSW, 2291<br/>Sydney: +61 - (02) 9052 6460 | Newcastle: +61 - (02) 9052 6461

info@centricengineers.com.au www.centricengineers.com.au

Job Title: NEW WAREHOUSE Address: 40 PLATINUM COURT THRUGOONA NSW 2640 Job No: 24071 Discipline: Hydraulic

Distribution	Attention							Nu	mh	er	of	Cor	hie	\$					
Distribution	Attention							Nui					JIC	3 		_			<u> </u>
		1				_	_	_	+	_	_	_	_	$\rightarrow$	_	_	$\rightarrow$	_	+
					_	_	_		+	+	_	_	+	$\rightarrow$	_	_	_	_	+-
				$\left  \right $	_	$\rightarrow$	-		+	+	+	-	+	$\rightarrow$	_	$\rightarrow$	$\rightarrow$	-	+
			_		_	-	-	_	+	+	_	-	+	$\rightarrow$	_	_	-	-	+
				$\left  \right $		$\rightarrow$	-		╉	+	+	-	+	+	-	$\rightarrow$	+	-	+-
				$\left  \right $		$\rightarrow$	-		╉	+	+	-	+	+	-	$\rightarrow$	+	-	+-
						_	_		+	+	-	-	-	-	_	_	-	-	+-
									+										┿╸
Purpose: A = Approval C = Construction I = Info T = Te	ender P = Prelim	Р				_			$\downarrow$	_			_	_			_		$\perp$
Format: D = Dwg H = Hard Copy P = Pdf T = Plt		Р								$\perp$									
Method: C = Courier H = Hand M = Mail E = Email W	= Website	E																	
Date of Issue:	Day	30																	
	Month	05																	
	Year	25																	
Issued By:		IB																	
Document Title	Document No								R	levi	isic	on_							
	Нооо	P1																	
Cover Sheet, Legend & Drawing Schedule			-	$\vdash$		-+			+	+	+	+	-+	-+	-+	-+	-+	+	+
Hydraulic Specifications	H001	P1	-			-+	-	+	+	+	+	+	+	-+	-+	-+	$\rightarrow$	+	——
Site Services	H002	P1				-+		+	+	+	+	+	+	-+	-+	$\rightarrow$	-+	+	+
Ground Floor Plan Sanitary Drainage Layout	H100	P1		$\square$				$\square$	$\downarrow$	$\square$	$\square$		$\square$	$\square$	$\square$	$\square$	$\square$		$\perp$
Mezzanine Floor Plan Sanitary Drainage Layout	H101	P1																	
Roof Plan Sanitary Drainage Layout	H102	P1																	
Ground Floor Plan Water and Gas Layout	H200	P1																	
Details	H300	P1																	
																			+
									+	╈			+	+			+		+
						+			+	╉	-		+	+			+		+-
						$\rightarrow$	-		+	+	-	-	+	+	$\rightarrow$	-	+	-	+
				$\left  \right $		-		-	+	+	-	-	-	-	-		-	-	+
					_	_	_		+	+	_	-	-	_	_	_	_	-	+-
						_			+	+	$\rightarrow$	_	+	$\rightarrow$	_	$\rightarrow$	$\rightarrow$	_	+
						_	_	_			_	_						_	——
																			$\rightarrow$
																			+
						+		+	╈	╈	$\uparrow$	+	+	+	+	-		+	+
								+	╉	+	╉	+	+			$\neg$		+	+
				$\vdash$		-+		+	╉	+	+	+	+	+	-+	-+	+	+	+
			-	$\left  - \right $		$\dashv$	$\neg$	+	╉	+	+	+	+	+	$\dashv$	$\dashv$	+	+	+
				$\left  - \right $		-+	$\neg$	+	╉	+	+	+	+	+	$\dashv$	$\dashv$	+	+	+-
				$\left  - \right $		-+		+	+	+	+	+	+	-+	-+	-+	-+	+	+
				$\left  - \right $			-	-+	+	+	+	+	+		-+	-+		+	+
				$\square$		-+		$\square$	$\downarrow$	-+	$\square$	$\square$	$\square$			$ \rightarrow$		$\square$	$\perp$
				$\square$		$\square$										$\square$			$\perp$
						Τ	1		Τ	Τ	Τ		Τ	Τ	Τ	T	Τ		
·			-				-		-		-		-	-					